



Wavetrend Wireless Reader

Product Code: L-RX1000

Description: Wireless Reader

The **L-RX1000** Wireless Reader detects and decodes RF transmitted signals from the Wavetrend family of tags. Interpreted data is converted into electrical information that is passed through the Wifi port.


The **L-RX1000** readers can be used in a one-one Ad-Hoc mode or connected via a wireless router / hub on a wireless network. The communication between the host PC and the wireless reader is by IEEE 802.11b protocol standard.



Features

- Supports WLAN 802.11b
- Easy configuration through a web interface
- Embedded Web Server for additional web pages
- Email capabilities
- Password Protection
- High performance data throughput
- 128 bit WEP Encryption
- Readers are powered by a 12v - 1.5amp power supply, centralised or distributed PSU topology may be used.
- Reader status indication by LED's.
- ESD protection as specified by FCC and CE requirements.
- Conformance to the RF standards required by the internationally accepted regulatory bodies: i.e. FCC, CE and ETSI.
- Sensitivity adjustment, and reader addressing done remotely via PC software application.
- Reader programming (configuration) done dynamically via PC software.

Basic Configuration





Typical read ranges of Wavetrend Tags with various antennas

(Distances may vary depending on the ambient RF environment)

(The following tests were conducted in free air)

L-RX1000

	Min	Max
Antenna Type	Range (metre)	Range (metre)
None	0.2	7
L-AN200 (Stub)	1	30
L-AN100 (Whip)	3	35
L-AN300 (Patch)	3	100
RSSI threshold	64	130

Specifications

RF Specifications

Rx Frequency	433 Mhz
Demodulation	ASK
Sensitivity	- 103 dBm
Stability	2ppm / °C
RF Input	50 Ohm BNC (Female)

Electrical Specifications

Supply Voltage	6 V DC – 16 V DC
Max current consumption	±72 mA to 80 mA
ESD protection	2 kV Human Body Model

Protocol Specifications

Standard Data Rate (Baud)	Wireless 10/100Mbit/s
Interface	Wireless 802.11b

Environmental

Operational temperature	- 10° C to + 60° C
Storage temperature	-20° C to + 70° C
Humidity	5 % to 90 % (non condensing)

Physical

Size	146 mm x 111 mm x 24 mm
Weight	360 grams
Colour	Silver
Type of material	Aluminium
Input/Output Connections	1 x Serial, 1x 802.11b interface,





L - Series

Product Information Sheet

Certification

The following standards applied in accordance with Article 5 of the directive, 1999/5/EC:

- EN 300 220-1 V1.2.1 (1997-11)
- ETS 300 683 (1997-03).
- FCC

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference, and
- This device must accept any interference received, including interference that may cause undesired operation
- All certifications are pending until the official release of the product

Summary of tests

Effective radiated power	25 MHz - 4 GHz
EN55022	Radiated emissions 30 MHz – 1GHz
EN55022	Conducted emissions 150 kHz – 30 MHz
EN61000-4-3	Radiated immunity 80 MHz – 1GHz, excl 433 MHz ± 20 MHz
EN61000-4-4	Electrical fast transients
EN61000-4-2	Electrostatic discharge
EN61000-4-6	Conducted immunity 150 kHz – 80 MHz



Wavetrend (UK) Ltd
Parkshot House
5 Kew Road
Richmond
Surrey
TW9 2PR
England
Tel +44 (0) 20 8334 8400
Fax +44 (0) 20 8334 8401
www.wavetrend.net
sales-uk@wavetrend.net



Wavetrend Technologies, Inc.
13912 NE 31st Place
Bellevue
WA 98005
USA
Tel +1 425 785 4781
Fax +1 425 869 4150
www.wavetrend.net
sales-usa@wavetrend.net



Wavetrend (Pty) Ltd
Wavetrend House
Hammets Crossing Office Park
Selborne Rd
Fourways
Johannesburg
South Africa
Tel +27 (11) 462 2633
Fax +27 (11) 462 6316
www.wavetrend.net
sales-sa@wavetrend.net