

Reader

Product Code: L-RX300

Description: Reader – RS232

The Reader connects directly to an available serial port on the computer. The Reader detects the presence of all Wavetrend™ L-series compatible Active Tags within its read range and continuously streams the data to the serial port.

The reader is of a crystal stabilised Superheterodyne RF receiver design.



Features:

- Plugs into any Serial port with a DB9 (male) connector.
- No external power supply is needed as this is supplied by the PC's communication port.
- The Baud rate of outgoing data is 57600.
- The Received Signal Strength indicator is appended to the Tag information, which is passed onto the serial port.
- Small compact design.
- The antennae is enclosed within the product housing.

Applications:

PC access control (PCAC) applications when used in conjunction with Wavetrend PCAC software (product code: L-SY100). The PSION handheld computer reader also makes use of this reader (product code: L-SW600).

Specifications:

Environmental

Operational temperature	- 40° C to + 75° C
Storage temperature	- 40° C to + 85° C
Humidity	5% to 90% (non condensing)

Electrical

Comm port Baudrate	57600 bps
Receive Frequency	433 MHz
Bandwidth	± 300KHz
Sensitivity	- 85dB
Power supply	+ 7Vdc
Current Consumption	< 11mA

Physical

Size (Reader)	32 mm x 33 mm x 14 mm
Colour	Dark Grey (Clariant 04-600 2%)
Type of material	Fire resistant ABS

Wavetrend (Pty) Ltd.
Wavetrend House
Hammets Crossing Office Park
Selbourne Rd
Fourways
Johannesburg
South Africa
Tel +27(11)462-2633
Fax +27(11)462-6316



Wavetrend Inc.
13912 NE 31st Place
Bellevue
USA

Tel +1-206-949-6394

sales@wavetrend.net

Wavetrend UK Ltd.
1st Floor, 7 Mallard Court,
Mallard Way, Crewe Business Park, Crewe,
Cheshire
England
CW1 6ZQ

Tel +44-1270-214-433
Fax +44-1270-214-420

